


MODEL 882 ADV-X

STRUTTED INTERIOR HIGH SPEED FABRIC DOOR



Lightweight and Durable

Ideal for manufacturing, warehouse and distribution facilities,
the Model 882 ADV-X is built to last.

High Cycle Design

- Springless design requires minimal interruption for maintenance
- Direct-mounted gear drive minimizes wear and tear
- Variable frequency drive eliminates sudden jolts from door start/stop

Strut Design

- Allows for quick section replacement, while reducing curtain deflection under pressure

Applications

- Manufacturing/Heavy Manufacturing
- Warehouse/Distribution
- Food and Beverage
- Cold Storage

Low Maintenance

- Breakaway design impact detection and push button self-repair; plug and play wiring

Technical Information

Attributes	General Specifications
Application	Interior
Maximum width	16'
Maximum height	15'
Opening speed	Up to 65"/sec
Closing speed	Up to 40"/sec
Break-away self reset	Yes
Pressure/wind resistance*	Up to 4.0 PSF or 76 MPH
Operational pressure**	Up to 2.5 PSF or 53 MPH
Wind strut	1" Strut Standard
Door panel	2 layers of PVC-coated polyester with 1 layer of polyester weave
Vision	20" high windows spaced evenly across width of door
Operation	Direct drive motor and gearbox system with a door stop device
Control	Variable frequency drive NEMA 4X cULus listed Onboard self diagnostic and service reminder Built-in padlockable field disconnect
Obstruction detection	Infrared sensors mounted in-plane to the door curtain at 18" and 50"- 54" from floor
Reversing safety edge	Wireless reversing edge
Electrical availability	120V AC 1PH, 230V AC 1PH, 230V AC 3PH, 460V AC 3PH, 575V AC 3PH

* Pressure/wind resistance value is the ultimate pressure tested at door width of 16'. The MPH is determined in accordance to ASCE 7-10 EXP B.

**Operational pressure value is the pressure tested up to 100,000 cycles at door width of 16'.

Door Options

- 20" high windows spaced evenly across width of door
- Multiple actuation options – push button, motion detector, radio control, key switch, pull switch, loop detector, treadle switch
- Signaling devices – red/green LED warning light, horn/strobe combination, rotating warning light

Color Options



Red



Blue



Gray



Black



5-Year Limited Warranty

Standard color for guides, brackets, struts and bottom bar is yellow. 197 optional RAL powder coat colors are available.