



- 1 - TOP HINGE ASSEMBLY
- 2 - BOTTOM HINGE ASSEMBLY
- 3 - 1/2" THICK BLACK ABRASION RESISTANT RUBBER
- 4 - 1/2" THICK CLEAR SAFETY ACRYLIC WINDOW
- 5 - 11 ga. ROLL-FORMED STEEL FRAME

*** RECOMMENDED FRAMING REQUIREMENTS:
 1/4" THICK x 6" WIDE FACE STEEL FRAME MOUNTED TO A SOLID FOUNDATION.

DOOR OPENING:

_____ W x _____ H

- DOUBLE
- SINGLE

QUANTITY: _____

OPTIONS

(CHECK BOX IF APPLICABLE)

- TRANSOM
- KICKPLATES (UP TO 48" HIGH)
- "D" BUMPERS
- 90° FLOOR-MOUNT JAMB GUARDS
- 90° JAMB-MOUNT JAMB GUARDS
- 90°-135° JAMB-MOUNT JAMB GUARDS
- JAMB GUARDS
- 90°-135° WIDE ANGLE HINGE
- GALVANIZED FRAME & SHAFT
- 8 ga. STEEL FRAME
- CUSTOM WINDOW (20" HIGH)
- EXTENSION "U" BRACKETS
- WELD PLATES
- HOLD OPEN DEVICE
- MAGNETIC CLOSURE
- CHANNEL LOCKING DEVICE
- CHAIN LOCKING COLLAR

TRANSOM

KICKPLATE



S. S. QUOTE REF. # _____
 CUSTOMER _____
 APPROVED BY: _____
 P/O No.: _____
 DATE: _____

SERIES 4000 - MODEL 4100
 FLEXIBLE RUBBER IMPACT DOOR
 DATE: FEB-03-09 SCALE: 1:32
 DRAWN: GK,OC DWG NO: L4100-A