



\*\*\* RECOMMENDED FRAMING REQUIREMENTS:  
 1/4" THICK x 8" WIDE FACE STEEL FRAME MOUNTED TO A SOLID FOUNDATION.

- 1 - TOP HINGE ASSEMBLY
- 2 - BOTTOM HINGE ASSEMBLY
- 3 - 1/8" ALUMINUM FACE PANEL
- 4 - DOUBLE PANE CLEAR LEXAN SAFETY WINDOW w. SECURITY BARS
- 5 - 11 ga. ROLL-FORMED STEEL SIDE FRAME
- 6 - PVC EDGE TRIM c/w GASKET
- 7 - 11 ga. x 1 1/2" SQUARE TUBULAR ALUMINUM DOOR FRAME
- 8 - 1 1/2" FOAM INSULATION
- 9 - 42" HIGH SUPERPLASTIC SPRING BUMPERS
- 10 - TOP CANE BOLT ASSEMBLY
- 11 - BOTTOM CANE BOLT ASSEMBLY
- 12 - CHAIN LOCKING COLLAR

DOOR OPENING: \_\_\_\_\_ W x \_\_\_\_\_ H

QUANTITY: \_\_\_\_\_

DOUBLE       SINGLE

OPTIONS

(CHECK BOX IF APPLICABLE)

- DOUBLE DUTCH

S. S. QUOTE REF. # \_\_\_\_\_

CUSTOMER \_\_\_\_\_

APPROVED BY: \_\_\_\_\_

P/O No.: \_\_\_\_\_

DATE: \_\_\_\_\_

**SUPER SEAL**

SERIES 4500 - MODEL 4500APO  
 HEAVY DUTY RIGID INSULATED IMPACT DOOR

DATE: NOV-23-04      SCALE: 1:32

DRAWN: GK,OC      DWG #: L45APO-A